Kebusol-Primer HT
PRODUCT DATA SHEET

- Adhesion-promoting primer
- Bitumen base
- Consumption: 0,2 l/m²
- Up to 50 °C

Kebusol-Primer HT is an adhesion-promoting, solvent containing primer based on bitumen and unsaponifiable resins.
It can be used up to a continuous operating temperature of 50 °C.

Kebusol-Primer HT ensures high peel resistance of Kebu bitumen tapes and Kebulen Heat shrinkable sleeve MSM C 50. In combination with the suitable products, it is suitable for the coating of pipes, pipe fittings and welded joints according to DIN 12068, DIN 30672 and ISO 21809-3.
The primer is suitable for steel and other metal surfaces, as well as for factory coatings made of PE, PP, EP and PUR.
The primer completely wets rough surfaces and binds dust residues.

FORMS OF DELIVERY

	Container content [l]
Kebusol-Primer HT	1
	5
	10
	30

Other dimensions on request

PROPERTIES

Property	Unit	Typical value
Drying time	min	5 - 15
Consumption	l/m²	≈ 0,20
Density	g/cm³	≈ 0,80 – 0,90

The information given in this publication is based on our knowledge and experience. The hints and instructions for use given therein have been compiled to the best of our knowledge on the basis of our tests and experience. Best results will be obtained if our products are used in a proper and expert way. Any protected rights and existing laws and regulations must be complied with the recipient. In all other respects our general terms and conditions shall apply.
-- Rev.: 01_04.03.2022 --

Kebulin-Gesellschaft Kettler GmbH & Co. KG
Ostring 9 | D-45701 Herten-Westerholt
Tel. +49 209 9615-0 | Fax +49 209 9615-190 | info@kebu.de | www.kebu.de