Page 1 / 10 EN Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 10.08.2015 / 03 Replaces revision of / Version: 06.06.2013 / 02 PDF print date: 10.08.2015 Kebu Bitumen-Tape "Special"

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Kebu Bitumen-Tape "Special"

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant indentified uses of the substance or mixture:

This is an article **Uses advised against:** No information available at present.

1.3 Details of the supplier of the safety data sheet

Kebulin-Gesellschaft Kettler GmbH & Co. KG, Ostring 9, D-45701 Herten-Westerholt Telephone ++49(0)209/9615-0, Fax ++49(0)209/9615-190

1.4 Emergency telephone

Advisory office in case of poisoning:

Tel.:

Telephone number of the company in case of emergencies:

Tel.: ++49(0)209/9615-0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) 1272/2008 (CLP)

Not classified

2.1.2 Classification according to Directives 67/548/EEC and 1999/45/EC (including amendments).

Not classified

2.2 Label elements

2.2.1 Labeling according to Regulation (EC) 1272/2008 (CLP)

Not applicable

2.2.2 Labeling according to Directives 67/548/EEC and 1999/45/EC (including amendments). This is an article.

Symbols: Not applicable Indications of danger: ---R-phrases: S-phrases: Additions: n.a.

2.3 Other hazards

Will cause burns if hot material contacts eyes. Will cause burns if hot material contacts skin.

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not includes under XIII of the regulation (EC) 1907/2006.

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

Asphalt, oxidized	
Registration number (ECHA)	01-2119498270-36
Index	-
EINECS, ELINCS	265-196-4
CAS	64742-93-4
content %	10 - 100
Classification according to Directive 67/548/EEC	Not classified
Classification according to Regulation (EC) 1272/2008 (CLP)	Not classified

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

If inhaled, remove to fresh air. Get medical attention if symptoms appear

Skin contact

Cold Product - Wash contaminated skin with soap and water. Remove contaminated clothing and wash underlying skin as soon as reasonably practicable.

Hot Product - Flood skin with cold water to dissipate heat, cover with clean cotton or gauze, obtain medical advice immediately.

Eye contact

Cold product - Wash eye thoroughly with copious quantities of water, ensuring eyelids are held open.

Obtain medical advice if any pain or redness develops or persists.

Hot product - Flood with water to dissipate heat. In the event of any product remaining, do not try to remove it other than by continued irrigation with water. Obtain medical attention immediately.

Ingestion

Typically no exposure pathway

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

4.3 Indication of any immediate medical attention and special treatment needed

Where skin burns occur the area should be immediately immersed in cold water until the product is thoroughly cooled. Do not attempt to remove the product from the skin as it provides an air-tight sterile covering over the burn which will eventually fall away with the scab as the burn heals.

If for any reason the product must be removed, this can be done using a slightly warmed medicinal liquid paraffin. Kerosine and other solvents should never be used.

All burns should receive medical attention.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

In case of fire, use water fog, foam, dry chemical or carbon dioxide extinguisher or spray. **Unsuitable extinguishing media** Do not use water jet.

Do not use water jet.

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Toxic gases.

5.3 Advice for firefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

Page 3 / 10 EN Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 10.08.2015 / 03 Replaces revision of / Version: 06.06.2013 / 02 PDF print date: 10.08.2015 Kebu Bitumen-Tape "Special"

6.1 Personal precautions, protective equipment and emergency procedures No special measures required.

6.2 Environmental precautions

Normally not necessary.

6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Contact with hot product may cause burns. Put on appropriate personal protective equipment (see Section 8). Avoid contact with skin. Avoid contact with eyes. If splashing is likely to occur wear a full face visor or chemical goggles as appropriate. Do not spray onto wet road surfaces or when rain is forecast as any resultant run-off could contaminate ditches and drains. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells. Store product closed and only in original packing. Store at room temperature. Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters Occupational exposure limits

No exposure limit value known.

Asphalt, oxidised						
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental compartment		-			
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,9	mg/m³ 8 h	NIOSH

Remarks: The DNEL does not represent a regulatory exposure limit but needs to be considered during workplace risk assessments.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Page 4 / 10 EN Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 10.08.2015 / 03 Replaces revision of / Version: 06.06.2013 / 02 PDF print date: 10.08.2015 Kebu Bitumen-Tape "Special"

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable. Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs. Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Cold material: wear safety glasses with side shields.

Hot material: to prevent thermal burns wear a helmet, full face visor and heat resistant neck flap / apron. Chemical splash goggles.

Skin protection - Hand protection:

Cold material: Wear chemical resistant gloves. Recommended: nitrile gloves.

Hot material: to prevent thermal burns wear heat resistant and impervious gauntlets/gloves.

Protective gloves must give suitable protection against mechanical risks (i.e. abrasion, blade cut and puncture).

Do not re-use gloves. Protective gloves will deteriorate over time due to physical and chemical damage.

Inspect and replace gloves on a regular basis. The frequency of replacement will depend upon the circumstances of use. Protective hand cream recommended.

Skin and body:

Cold material:

Wear impervious coveralls covering the full body and limbs.

Refer to standard: ISO 11612

Refer to standard: EN 1149

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination.

Chemical resistant boots.

When the risk of skin exposure is high (from experience this could apply to the following tasks: cleaning work, maintenance and service, filling and transfer, taking samples and cleaning up spillages) then a chemical protective suit and boots will be required.

Work clothing / overalls should be laundered on a regular basis. Laundering of contaminated work clothing should only be done by professional cleaners who have been told about the hazards of the contamination. Always keep contaminated work clothing away from uncontaminated work clothing and uncontaminated personal clothes.

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Thermal hazards:

Hot material: Wear impervious and heat resistant coveralls covering the full body and limbs.

Precautions are required to prevent protective clothing from accidentally trapping product against the skin.

Trouser legs should be worn over protective boots. The sleeve cuffs of protective clothing should be worn over protective gloves / gauntlets.

Protection should be provided for exposed areas of the neck and head. As appropriate, a heat resistant and impervious hood, a neck cover / apron or a neck flap can be used to protect from burns. Hard hat. Heat resistant boots. Footwear highly resistant to chemicals.

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

Not information available at present.

Page 5 / 10 EN Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 10.08.2015 / 03 Replaces revision of / Version: 06.06.2013 / 02 PDF print date: 10.08.2015 Kebu Bitumen-Tape "Special"

SECTION 9: Physical and chemical properties

Solid

9.1 Information on basic physical and chemical properties

Physical state: Colour: Odour: Odour threshold: pH-value: Melting point/freezing point: Initial boiling point and boiling range: Flash point: Evaporation rate: Flammability (solid, gas): Lower explosive limit: Upper explosive limit: Vapour pressure: Vapour density (air = 1): Density: Bulk density: Solubility(ies): Water solubility: Partition coefficient (n-octanol/water): Auto-ignition temperature: Decomposition temperature: Viscosity: Explosive properties: Oxidising properties:

black Characteristic Not available n.a. 100 - 130°C (Softening Point) Not determined Open cup: > 220 °C Not available Not determined Not determined Not determined Not determined Not determined 1,1 - 1, 3 g/mln.a. insoluble in water Insoluble Not determined > 400 °C Not determined Not determined Product is not explosive No

9.2 Other information

No additional information

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.

10.4 Conditions to avoid

Avoid excessive heat.

10.5 Incompatible materials

See also section 7. None known.

10.6 Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Possibly mor information on health effects, see Section 2.1 (classification).

	opeela					
Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral						n.d.a
route:						

Safety data sheet accord Revised on / Version: 10.			10 1307/20			
Replaces revision of / Vers	sion: 06.06.20	13 / 02				
PDF print date: 10.08.2015						
Kebu Bitumen-Tape "Spec	al"				1	
Acute toxicity, by dermal						n.d.a
route: Acute toxicity, by						n.d.a
inhalation:						11.u.a
Skin corrosion/irritation:						n.d.a
Serious eye						n.d.a
damage/irritation						
Respiratory or skin						n.d.a
sensitisation:						
Germ cell mutagenicity: Carcinogenicity:						n.d.a n.d.a
Reproductive toxicity:						n.d.a
Specific target organ						n.d.a
toxicity - single exposure (STOT-SE)						
Specific target organ						n.d.a
toxicity - repeated						
exposure (STOTRE)						
Aspiration hazard:						n.d.a
Respiratory tract irritation:						n.d.a
Repeated dose toxicity: Symptoms:	}					n.d.a n.d.a
Other information						This is an article.
						The le an article.
Asphalt, oxidised						
Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral	LD50	>5000	mg/kg	Rat	OECD 401 (Acute	Based on Vacuum
route:					Oral Toxicity)	residue
Acute toxicity, by dermal	LD50	> 2000	mg/kg	Rabbit	OECD 402 (Acute	Based on Vacuum
route: Acute toxicity, by	LC50	>5,7	mg/l/4 h	Rat	Oral Toxicity) OECD 403 (Acute	residue Based on oxidised
inhalation:	2030	>0,1	111g/1/4 11	Παι	Inhalation Toxicity)	Bitumen
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
				-	Dermal	-
					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation					Eye	
Respiratory or skin					Irritation/Corrosion) OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	Based on Vacuum
conomoulon.						residue
Germ cell mutagenicity:				Mammalian	OECD-äquivalent	Positiv
- •				-Animal	474	Based on oxidised
0			ļ	In Vitro	0500	Bitumen
Germ cell mutagenicity				Non- mammalian	OECD- 471	Positiv Based on Bitumen
				species	+/ 1	Daseu UN DILUMEN
				In Vitro		
				Unspecified	OECD-äquivalent	Negativ
				In vivo	474	Based on oxidised
				la si	Net with the	Bitumen
				In vivo	Not guideline	Negativ Based on Bitumen
Carcinogenicity:						Daseu un Dilumen
Reproductive toxicity:						
Specific target organ toxicity - single exposure						Not classified
(STOT-SE)						Not alcosific -
Specific target organ toxicity - repeated						Not classified
	1	1	1	1		

Page 7 / 10 EN	a to Docula	tion (FC) No 1007	20000	Annov II		
Safety data sheet accordin		ation (EC) NO 1907	/2006,	Annex II		
Revised on / Version: 10.0							
Replaces revision of / Versi	on: 06.06.20	13 / 02					
PDF print date: 10.08.2015							
Kebu Bitumen-Tape "Special Aspiration hazard:	al"						
1							
Respiratory tract irritation:							
Symptoms:							
Not classified. Based on av	ailable data,	the class	ification cr	iteria ar	e not met.		
	SE	CTION	l 12: Ec	ologio	cal inform	nation	
Possibly mor information or							
Kebu Bitumen-Tape				(01400111	ioution).		
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:					Ŭ		n.d.a.
Toxicity to daphnia:							n.d.a.
Toxicity to algae:							n.d.a.
Persistence and							n.d.a.
degradability:							
Bioaccumulative							n.d.a.
potential:							
Mobility in soil:							n.d.a.
Results of PBT and							n.d.a.
vPvB assessment							
Other adverse effects:							n.d.a.
Aspalt, oxidised		·					
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to Microorganism:	LL50	40 h	>1000	mg/l			Growth inhibition
Toxicity to Algae:	EL50	72 h	>1000	mg/l			(growth rate)
Toxicity to fish:	LL50	96 h	>1000	mg/l			Mortality
Toxicity to Microorganism:	NOEL	40 h	>1000	mg/l			growth inhibition
Toxicity to daphnia:	LL50	48h	>1000	mg/l			Mortality
Toxicity to fish:	LL50	28 d	>1000	mg/l			Mortality
Toxicity to fish:	NOEL	28 d	>1000	mg/l			Mortality
Toxicity to daphnia:	NOEL	21 d	>1000	mg/l			Reproduction
Persistence and degradability:							Not determined
Bioaccumulative		+					Not determined
potential:							
Mobility in soil:							Spillages are
woonity in soil.							unlikely to penetrate
							the soil
Results of PBT and							No
vPvB assessment							
				1	i		1

SECTION 13: Disposal considerations

13.1 Waste treatment methods For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC) 17 03 02 bituminous mixtures other than those mentioned in 17 03 01 Recommendation:

Pay attention to local and national official regulations

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations Recommendation: Recycling

Page 8 / 10 ΕN Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 10.08.2015 / 03 Replaces revision of / Version: 06.06.2013 / 02 PDF print date: 10.08.2015 Kebu Bitumen-Tape "Special"

SECTION 14: Transport information

General statements

This product is not regulated for carriage according to ADR/RID, IMDG, ICAO/IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labeling see Section 2. Hazard class for water (Germany): WGK 0 Observe restrictions:

VOC (1999/13/EC)

n.a. n.a.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

These details refer to the product as it is delivered.

n.a.

Revised sections: The following statements are the indicated R-phrases / H-phrases and classification codes (GHS/CLP) for the ingredients (listed in Section 3).

AC **Article Categories**

Any abbreviations and acronyms used in this document: acc., acc. to according, according to ACGIH American Conference of Governmental Industrial Hygienists ADR Accord europeen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOEL Acceptable Operator Exposure Level AOX Adsorbable organic halogen compounds approx. approximately Article number Art., Art. no. ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP) BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, BAuA Germany) BCF **Bioconcentration factor** Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation) BGV Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BHT **BMGV** Biological monitoring guidance value (EH40, UK) BOD Biochemical oxygen demand BSEF Bromine Science and Environmental Forum bw body weight CAS **Chemical Abstracts Service** CESIO Comité Europeen des Agents de Surface et de leurs Intermédiaires Organiques CIPAC **Collaborative International Pesticides Analytical Council** CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic COD Chemical oxygen demand Cosmetic, Toiletry, and Fragrance Association CTFA DMEL **Derived Minimum Effect Level Derived No Effect Level** DNEL DOC Dissolved organic carbon **DT50** Dweil Time - 50% reduction of start concentration DVS Deutscher Verband für Schweißen und verwandte Verfahren e.v. (= German Association for Welding and Allied Processes) dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EC European Community ECHA **European Chemicals Agency** EEA European Economic Area

Page 9 /	/ 10 EN
	lata sheet according to Regulation (EC) No 1907/2006, Annex II
	l on / Version: 10.08.2015 / 03
	s revision of / Version: 06.06.2013 / 02
	nt date: 10.08.2015
	tumen-Tape "Special"
EEC	European Economic Community
	European Inventory of Existing Commercial Chemical Substances
	European list of Notified Chemical Substances
EN	European Norms
EPA	United States Environmental Protection Agency (United States of America)
ERC	Environmental Release Categories
ES	Exposure scenario
etc.	et cetera
EU	European Union
EWC	European Waste Catalogue
Fax.	Fax number
gen.	general
ĞHS	Globally Harmonized System of Classification and Labelling of Chemicals
GWP	Global warming potential
HET-CA	
HGWP	Halocarbon Global Warming Potential
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IBC	Intermediate Bulk Container
IBC	(Code) International Bulk Chemical (Code)
IC	Inhibitory concentration
IMDG-co	ode International Maritime Code for Dangerous Goods
in cl.	including, inclusive
IUCLID	International Uniform Chemical Information Database
LC	lethal concentration
LC50	lethal concentration 50 percent kill
LCLo	lowest published lethal concentration
LD	Lethal Dose of a chemical
LOSO	Lethal Dose, 50% kill
LDLo	Lethal Dose Low
LOAEL	Lowest Observed Adverse Effect Level
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest Observed Effect Level
LQ	Limited Quantities
	L International Convention for the Prevention of Marine Pollution from Ships
n.a.	not applicable
n.av.	not available
n.c.	not checked
n.d.a.	no data available
NIOSH	National Institute of Occupational Safety and Health (United States of America)
NOAEC	
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
NOEL ODP	No Observed Effect Level
OECD	Ozone Depletion Potential Organisation for Economic Co-operation and Development
	Organisation for Economic Co-operation and Development
org. PAH	organic polycyclic aromatic hydrocarbon
PAH PBT	persistent, bioaccumulative and toxic
PDI PC	Chemical product category
PE	Polyethylene
PNEC	Predicted No Effect Concentration
POCP	Photochemical ozone creation potential
ppm	parts per million
PROC	Process category
PTFE	Polytetrafluorethylene
REACH	• •
,.011	the Registration,
Evaluatio	on, Authorisation and Restriction of Chemicals)
	-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other
	numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for
	processing a submission via REACH-IT.
RID	Reglement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation
	concerning the International Carriage of Dangerous Goods by Rail)
SADT	Self-Accelerating Decomposition Temperature
SAR	Structure Activity Relationship

Page 10 / 10 EN Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 10.08.2015 / 03 Replaces revision of / Version: 06.06.2013 / 02 PDF print date: 10.08.2015 Kebu Bitumen-Tape "Special"
SU Sector of use
SVHC Substances of Very High Concern
Tel. Telephone
ThOD Theoretical oxygen demand
TOC Total organic carbon
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
WE.L-TWA, WEL-STEL WEL-TWA = Workplace Exposure limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure limit - Short-term exposure lim it (1 5-minute reference period) (EH40, UK).
WHO World Health Organization
wwt wet weight
These statements were made by:

Kebulin-Gesellschaft Kettler GmbH & Co. KG Ostring 9, D-45701 Herten-Westerholt Telefon: +49 (0)2 09 96 15-0 Fax: +49 (0)2 09 96 15 190 e-mail: info@kebu.de

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.